

Simplifying NFPA 110 Requirements + Best Practices For Generators, Automatic Transfer Switches, Paralleling Switchgear and Related Components

AS ALWAYS, YOU SHOULD CONSULT YOUR AUTHORITY HAVING JURISDICTION (AHJ) FOR ALL CODE RELATED MATTERS. THE INFORMATION PROVIDED IN THIS PRESENTATION IS THE INTERPRETATION OF THE CODE AND BEST PRACTICES OF THE PRESENTER, MONTY HAGBERG.

LONHEART CRITICAL POWER SPECIALI

A LITTLE ABOUT US

- Established in 1999
- Service over 3,000 unique accounts
- Not affiliated with any Original Equipment Manufacturer
- Provide more technically-competent services and solutions than OEM competitors by focusing on maintenance, repairs, replacements and upgrades - not generator sales.
- Veteran Owned
- Most EGSA Certified Journeymen in the Midwest
- In-House 24/7 Engineering Team
- Comprehensive On-Site Training





A LITTLE ABOUT YOUR PRESENTERS: MONTY AND JORDAN

- A combined 23 years of generator service support & sales to engineers, plant operations professionals, and facility directors just like you.
- Most times, this training is provided *in-person*, on-site with your own equipment.
- Other times are *in-person* for large groups.
- This is our first remote webinar....

We need your questions to take it to the next level for everyone!!!

And, if you help by asking questions...



3



THSWEBINAR

WILL BLOW YOUR MIND.

makeameme.org



whoa there pal ...





PROTECT YOUR EYES

Always wear safety glasses PROTECT YOUR EARS

Always wear ear protection

we get it have done which which prevention of the set o

1. . .

, nam and a man high and and fait was seen that bill bill and a same and bits super a same a more that a same are same and a same are same and a same are same and a same are same ar

Statistic Activity Constants Statistics

PROTECT YOUR SKIN

Always wear flame retardant clothing and gloves

And Design in the state of the state

Contraction of the Contraction o



whoa there pal ...



PROTECT YOUR EYES

Always wear safety glasses PROTECT YOUR EARS

Always wear ear protection PROTECT YOUR SKIN

Always wear flame retardant clothing and gloves





whoa there pal ...





PROTECT YOUR EYES

Always wear safety glasses PROTECT YOUR EARS

Always wear ear protection PROTECT YOUR SKIN

Always wear flame retardant clothing and gloves







So....What's New?

The first round of changes in 13 years!!! Sometimes change can be *uncomfortable*....





NFPA 110

So....What's New?

But we want you to be comfortable with THESE changes!!

- Differentiation between <u>Diesel</u> and <u>Natural Gas</u> generators Annual Load Bank Testing duration is reduced and testing levels are relaxed
- --
- 4-hour Load Testing is required for <u>all generators every 36 months</u>
- Fuel Quality Test is required annually
- Transfer Switch Maintenance and Testing Program is required _
- Paralleling Switchgear Maintenance and Testing Program is required
- Breaker exercising and testing is required —
- Maintenance-free batteries are allowed
- A monthly-style test is required after repairs that "impact" operational reliability

- Here are a few key differences between the previous edition (1999) and the 2010 edition:



Key Terms LEVEL I VS. LEVEL Z SYSTEMS Level 1 systems refer to systems that are essential for safety to human life. For the sake of this discussion, were going to be talking about Level 1 systems.



When NFPA provides required percentages that must be met during testing, it is referring to the percentage of the <u>rated kW percentage</u> for the generator.



For this presentation, I will address spark-ignited as NATURAL GAS fueled engines

EPSS = EMERGENCY POWER SUPPLY SYSTEM

This term encompasses the generator(s), transfer switches, and related components

NFPA IIO







NFPA Requirements

- None

DAILY



GENERATOR

Best Practices

- Visual Inspection

Leaks, alarms, debris,

batteries, and

messages on the

control panel



TRANSFER SWITCH

NFPA Requirements

- None

Best Practices

- Visual Inspection Fault lights, position lights, and messages on the control panel

Our guide to a **VISVAL INSPECTION**



LEAKS

Look for leaks under the radiator, near the front of the engine, and at the block heater.





ALARMS

Look for alarms or messages at the generator control panels, remote annunciator panels, and ATS panels.





DEBRIS

Look for signs of rodent nesting and look for debris near the radiator.



BATTERIES

Look for pooling of electrolyte on top of the batteries, and look for corrosion on battery terminals.



NFPA Requirements

- _

WEEKLY



GENERATOR

- Visual Inspection and Documentation

- Specifically calls-out inspecting electrolyte levels (or battery voltage for maintenance free batteries)

Best Practices

Run the generator for 10 minutes to ensure proper start, no leaks, and the absence of alarms or warnings



TRANSFER SWITCH

NFPA Requirements

- Inspected weekly

Best Practices

- Visual Inspection of the exterior, lamps, and control panel



GENERATOR **NFPA Requirements**

Diesel Generator Testing

- for a minimum of 30 min.

Natural Gas Generator Testing

and oil pressure have stabilized

Best Practices

test (just like diesel generators)



- Operate the generator under building load

- To be exempt from annual load bank testing, load the generator to <u>30% or more</u>

(or maintain the minimum exhaust gas temperature recommended by the OEM but this info is not available in most cases)

- Operate the generator with the EPSS load for 30 minutes or until the water temperature

- Natural Gas generators should ran a FULL 30 minutes for the monthly

TRANSFER SWITCH **NFPA Requirements**

- Operate all connected transfer switches once per month

Best Practices

Rotate the ATS used to *initiate* each monthly test (to confirm the operation of each ATS's start signal)



Maintainable Batteries

NFPA Requirements

WEEKLY

- Inspect **Electrolyte Levels** in all battery cells.

MONTHLY

- Complete and document the testing of **Electrolyte Specific Gravity** in all cells

THEY GET THEIR OWN SLIDE BECAUSE THEY'RE THAT IMPORTANT!

Maintenance Free Batteries

NFPA Requirements

WEEKLY

- Inspect battery **Voltage**

MONTHLY

NOTE: NFPA-110 recommends batteries be replaced every 24-30 months (A.5.6.4.5.1)



(YES! THEY ARE ALLOWED!)

- Complete and document a battery **Conductance Test**



Here is a recommended conductance testing from Snap-On. Let us know if you want additional information!!









BATTERIES (THEY GET THEIR OWN SLIDE BECAUSE THEY'RE THAT IMPORTANT!)

Since the adoption of the 2012 Life Safety Code in 2016, dozens of our clients have requested their starting batteries be replaced with Maintenance Free batteries.

The requests are due to Joint Commission's enforcement of OSHA Instruction STD 01-08-002 which requires even stations in battery charging and maintenance areas.











GENERATOR

NFPA Requirements

Natural Gas

Engine and Generator Maintenance

- "Manufacturer's recommended Maintenance" to include inspection, testing all the main systems:
 - Starting/Electrical
 - Fuel
 - Cooling
 - Lube Oil
 - Air Intake/Exhaust
 - Controls and Safeties

Load Bank Testing - No longer required for natural gas generators

Best Practices

- Natural Gas generators should be load bank tested annually We identify more problems with the stability of natural gas engines than with diesel engines

- Laboratory analysis of <u>oil</u> and <u>coolant</u> samples

Diesel

Engine and Generator Maintenance

- "Manufacturer's recommended Maintenance" to include inspection, testing all the main systems:
 - Starting/Electrical
 - Fuel
 - Cooling
 - Lube Oil
 - Air Intake/Exhaust
 - Controls and Safeties

Load Bank Testing - If the monthly testing documentation does not meet the required load levels or exhaust temperatures, an annual Load Test is required. This test is typically performed with a load bank so the testing level can be 75% or greater for the last hour.

Load bank testing duration has been reduced from 2 hours to 1.5 hours

Load levels have been "relaxed"

Fuel Testing - Required



TRANSFER SWITCH

NFPA Requirements

- Transfer switches shall be subjected to a maintenance and testing program to include:
 - checking connections
 - inspection for overheating
 - checking for excessive contact erosion
 - removal of dust and dirt
 - replacement of contacts, if necessary

Best Practices

- In addition to NFPA Requirements, we recommend adding the following to annual switch maintenance:
 - Infrared scans or thermography of all cable connection points and the contactor assembly
 - Operation and testing of the bypass module if the ATS is a Bypass/Isolation switch
 - Confirm all time delays and pick-up / drop out settings







GENERATOR

NFPA Requirements

For Diesel Generators: A fuel quality test must be performed annually using testing approved by ASTM standards. But which ATSM standards? Please share what you know.



20

ANNUALLY

YOUR PARALLELING SWITCHGEAR NEEDS SOME LOVE TOO!



PARALLELING SWITCHGEAR

NFPA Requirements

- Paralleling switchgear shall be subjected to a maintenance and testing program to include:
 - checking connections
 - inspection for overheating
 - checking for excessive contact erosion
 - removal of dust and dirt
 - replacement of contacts, if necessary

Best Practices

Full function test to include all paralleling operations!



YEP! THERE'S MORE! LET'S TALK BREAKERS



NFPA Requirements

- Circuit breakers including main and feed breakers between the generator and the transfer switch shall be exercised.
- If circuit breaker is in excess of 600v it shall be exercised every 6 months and tested under overload conditions every 2 years.

Best Practices

Annual generator maintenance includes exercising the output breaker on the generator, HOWEVER ---- we suggest discussing this requirement with your electrician or the vendor who performs breaker maintenance on your utility switchgear.

BREAKERS







NFPA Requirements

Natural Gas

- 4-hour Load Test. Can be performed with building load (ATSs in EM position for 4 continuous hours).

Best Practices

- Natural Gas generators should be tested with a load bank to ensure proper operation at heavy load.

Diesel

- 4-hour Load Test. Must be performed at equal to or greater than 30% for 4 continuous hours
- If combined with an <u>annual</u> 1.5 hour test, the last hour must be equal to or greater than 75%
- If combined with a <u>monthly</u> 30minute test, the test must be initiated with an ATS and all connected ATSs must be transferred during the test.

TRIENNIALLY

(36 MONTHS)



TRANSFER SWITCH **NFPA Requirements**

- None

Best Practices

- No special recommendations for every 36 months, however we recommend powering-down each ATS every 5 years to torque lugs and cable connections

UARNING!!!!

12 SLIDES OF NFPA 110 CODE DETAILS ARE COMING!

HANG IN THERE ... WE'RE IN THE FINAL STRETCH ...

(THIS IS A GOOD TIME TO JOT DOWN QUESTIONS :-)

NFPA-110, 2010 edition

Chapter 8 Routine Maintenance and Operational Testing

8.1* General

shall be based on all of the following: (1) Manufacturer's recommendations (2) Instruction manuals (3) Minimum requirements of this chapter (4) The authority having jurisdiction

8.1.2 Consideration shall be given to temporarily providing a is out of service.

- 8.1.1 The routine maintenance and operational testing program
- portable or alternate source whenever the emergency generator





8.2* Manuals, Special Tools, and Spare Parts.

8.2.1 At least two sets of instruction manuals for all major components of the EPSS shall be supplied by the manufacturer(s) of the EPSS and shall contain.....

8.2.3 Special tools and testing devices necessary for routine maintenance shall be available for use when needed.

8.2.4 Replacement for parts identified by experience as high mortality items shall be maintained in a secure location(s) on the premises.

8.2.4.1 Consideration shall be given to stocking spare parts as recommended by the manufacturer.

(TESTING FOLLOWING REPAIRS)

8.3 Maintenance and Operational Testing

8.3.2 A routine maintenance and operational testing program shall be initiated immediately after the EPSS has passed acceptance tests or after completion of repairs that impact the operational reliability of the system.

8.3.2.1 The operational test shall be initiated at an ATS and shall include testing of each EPSS component on which maintenance or repair has been performed, including the transfer of each automatic and manual transfer switch to the alternate power source, for a period of not less than 30 minutes under operating temperature.



(ATS MAINTENANCE REQUIREMENT)

8.3.5* Transfer switches shall be subjected to a maintenance and testing program that includes all of the following operations:

(1) Checking of connections (2) Inspection or testing for evidence of overheating and excessive contact erosion

- (3) Removal of dust and dirt
- (4) Replacement of contacts when required



(PARALLELING GEAR MAINTENANCE REQUIREMENT)

8.3.6 Paralleling gear shall be subject to an inspection, testing, and **maintenance program** that includes all of the following operations:

(1) Checking of connections erosion

- (3) Removal of dust and dirt
- (4) Replacement of contacts when required

(2) Inspection or testing for evidence of overheating and excessive contact

(BATTERY REQUIREMENTS)

8.3.7* Storage batteries, including <u>electrolyte levels</u> or <u>battery voltage</u>, used in connection with systems shall be <u>inspected weekly</u> and maintained in full compliance with manufacturer's specifications.

8.3.7.1 Maintenance of lead-acid batteries shall include the <u>monthly testing</u> and recording of electrolyte specific gravity. Battery conductance testing shall be permitted in lieu of the testing of specific gravity when applicable or warranted.

8.3.7.2 Defective batteries shall be replaced immediately upon discovery of defects.



(BREAKER EXERCISE & TESTING REQUIREMENT)

8.4.7 EPSS circuit breakers for Level 1 system usage, including main and feed breakers between the EPS and the transfer switch load terminals, shall be exercised annually with the EPS in the "off" position.

8.4.7.1 Circuit breakers rated in excess of 600 volts for Level 1 system usage shall be exercised every 6 months and shall be tested under simulated overload conditions every 2 years.



(FUEL QUALITY TESTING REQUIREMENT)

8.3.8 A fuel quality test shall be performed at least <u>annually</u> using tests approved by ASTM standards.



(MONTHLY INSPECTIONS & TESTING)

8.4 Operational Inspection and Testing

8.4.1* EPSSs, including all appurtenant components, shall be inspected weekly and exercised under load at least monthly

8.4.2* Diesel generator sets in service shall be exercised at least once monthly, for a minimum of 30 minutes, using one of the following methods: (1) Loading that maintains the minimum exhaust gas temperatures as recommended by the manufacturer (2) Under operating temperature conditions and at not less than 30 percent of the EPS nameplate kW rating



(ANNUAL 1.5-HOUR LOAD TESTING FOR D)

8.4.2.3 Diesel-powered EPS installations that do not meet the requirements of 8.4.2 shall be exercised monthly with the available EPSS load and shall be exercised annually with supplemental loads at **not less than 50 percent** of the EPS nameplate kW rating for 30 continuous minutes and at **not less than75 percent** of the EPS nameplate kW rating for 1 continuous hour for a total test duration of not less than **1.5 continuous hours**.

8.4.2.4 Spark-ignited generator sets shall be exercised at least once a month with the available EPSS load for 30 minutes or until the water temperature and the oil pressure have stabilized.

8.4.3 The EPS test shall be initiated by simulating a power outage using the test switch(es) on the ATSs or by opening a normal breaker. Opening a normal breaker shall not be required.

(36-MONTH, 4-HOUR LOAD TESTING)

to terminate the test after 4 continuous hours.

function and then by operating the test function of all remaining ATSs, or ATSs that are part of the EPSS being tested *****

- 8.4.9* Level 1 EPSS shall be tested at least once within every 36 months.
- 8.4.9.2 Where the assigned class is greater than 4 hours, it shall be permitted
- **8.4.9.3** The test shall be initiated by operating at least one transfer switch test initiated by opening all switches or breakers supplying normal power to all



(36-MONTH, 4-HOUR LOAD TESTING)

8.4.9.5.1 For a diesel-powered EPS, loading shall be not less than 30 percent of the nameplate kW rating of the EPS. A supplemental load bank shall be permitted to be used to meet or exceed the 30 percent requirement.

8.4.9.5.2 For a diesel-powered EPS, loading shall be that which maintains the minimum exhaust gas temperatures as recommended by the manufacturer

8.4.9.5.3 For <u>spark-ignited EPSs</u>, loading shall be the available EPSS load.



(36-MONTH, 4-HOUR LOAD TESTING)

8.4.9.6 The test required in 8.4.9 [36-month test] shall be permitted to be combined with one of the monthly tests required by 8.4.2 and one of the <u>annual tests required by 8.4.2.3 as a single test.</u>

8.4.9.7 Where the test required in 8.4.9 is combined with the annual load bank test, the first 3 hours shall be at not less than [30%] the minimum loading required by 8.4.9.5 and the remaining hour shall be at not less than 75 percent of the nameplate kW rating of the EPS.









COMMENTS

We're Proud To Service

Mercyhealth Facilities Aspirus Health System North Central Health Care LindenGrove Communities St. Elizabeth Hospital **Ascension Calumet Hospital** St. Camillus Skilled Nursing

and over 3,000 other locations throughout Wisconsin, Illinois and Indiana





LIONHEARI CRITICAL POWER SPECIALISTS

*as of 6.2019

Veteran Owned | EGSA Certified | Independent | PowerAssured.com

Need Generator or Transfer Switch Service? 847.291.1413

Contact us for emergency service or a competitive proposal

